

MINI UHF CONNECTORS



2760 SERIES.

MINI-UHF SERIES

Connectors are designed for use as coaxial interconnections in cellular mobile telephone systems and similar applications where size, weight and cost factors are critical. These miniature 3/8"-24 thread size connectors provide an excellent RF performance for applications up to 2.5 GHz. This far out performs the limit of 300 MHz. For the standard 5/8"-24 thread UHF connectors. Mini UHF connectors combine excellent electrical characteristics, small size and lightweight at a relatively inexpensive cost for many coaxial connector applications

JACK CRIMP

Part Number	Ω	Cable
2760-11501	50	RG-58

Dimensions: 8.0, 16.0, 28.0, 36.0

CONEC. HEMBRA SOLDAR CABLE PARA PANEL

Part Number	Ω
2710-11556	50

Dimensions: 8.7, 5.6, 26.0, 3/8-24 UNF

CON. HEMBRA SOLDAR CABLE PARA PANEL

Part Number	Ω
2760-11557	50

Dimensions: 23.0, 16.0 SQ, 11.1, 9.9, Dia 2.4x4, 3/8-24 UNF

CONECTOR MACHO DE ENGASTE

Part Number	Ω	Cable
2760-11502	50	RG-58

Dimensions: 4, 7, 15.5, 3/8-24 UNF, 21.0, 7.5, 12.0

CONECTOR MACHO ENGASTE ACODADO

Part Number	Ω	Cable
2760-11503	50	RG-58

Dimensions: 3, 7.0, 14.0, 10.0 SQ, 7.5

HEMBRA DE ENGASTE PARA PANEL

Part Number	Ω	Cable
2760-11504	50	RG-174

Dimensions: 4, 7, 15.5, 3/8-24 UNF, 23.5, 7.5