

# SIDE ENTRY PCB JACK FCC-68



## 6810 SERIES. For PCB Solder. Side Entry PCB Jack

### Features

- Available in 4/4, 6/2, 6/4, 6/6, 8/6 and 8/8 circuits
- Insulator Material: Glass filled polyester UL 94V-0
- Contacts: Golden phosphor bronze 0.35mm thickness
- Available with or without Panel Stop
- Gold plating over nickel in Contact Area.
- Tin plating over nickel in Solder Area
- Mates with FCC-68 modular plugs

### Dimensional Information

### Ordering and Dimensional Information

Circuit Size	Part Number		Dimensions			
	W/O Panel Stop	With Panel Stop	A	B	C	D
4/4	6810 - T440	6810 - T441	13.72 (0.540)	11.18 (0.440)	7.62 (0.300)	1.27 (0.050)
6/2	6810 - T620	6810 - T621	15.75 (0.620)	13.21 (0.520)	10.16 (0.400)	1.27 (0.050)
6/4	6810 - T640	6810 - T641	15.75 (0.620)	13.21 (0.520)	10.16 (0.400)	3.81 (0.150)
6/6	6810 - T660	6810 - T661	15.75 (0.620)	13.21 (0.520)	10.16 (0.400)	6.35 (0.250)
8/6	6810 - T860	6810 - T861	17.78 (0.700)	15.24 (0.600)	11.43 (0.450)	6.35 (0.250)
8/8	6810 - T880	6810 - T881	17.78 (0.700)	15.24 (0.600)	11.43 (0.450)	8.89 (0.350)



### T = Contact Plating

- T = 4. 6μ" gold over 50μ" nickel
- T = 5. 15μ" gold over 50μ" nickel
- T = 6. 30μ" gold over 50μ" nickel
- T = 7. 50μ" gold over 50μ" nickel

