LOW PROFILE SHIELDED PCB JACK

7639 SERIES. For PCB Solder. Side Entry Shielded PCB Jack

Features

- Available in 6/2, 6/4, 6/6, 8/6, 8/8 and 10/10 circuits
- Insulator Material: Glass filled polyester UL 94V-0
- Contacts: Golden phosphor bronze 0.35mm thickness
- Available with or without panel stop
- Gold plating over nickel in Contact Area.
  Tin plating over nickel in Solder Area
- Mates with FCC-68 modular plugs
- Shielded: 0.25mm thickness Copper Alloy with Nickel

Dimensional Information



Ordering and Dimensional Information

Circuit Size	Part Number	Dimensions				
		A	B	C	D	E
6/2	**7639 – T621**	13.83(0.545)	10.16 (0.400)	1.27 (0.050)	15.74 (0.620)	13.72 (0.540)
6/4	**7639 – T641**	13.83(0.545)	10.16 (0.400)	3.81(0.150)	15.74 (0.620)	13.72 (0.540)
6/6	**7639 – T661**	13.83(0.545)	10.16 (0.400)	6.35 (0.250)	15.74 (0.620)	13.72 (0.540)
8/6	**7639 – T861**	15.86 (0.625)	11.43 (0.450)	6.35 (0.250)	17.78 (0.700)	15.75 (0.621)
8/8	**7639 – T881**	15.86 (0.625)	11.43 (0.450)	8.89 (0.350)	17.78 (0.700)	15.75 (0.621)
10/10	**7639 – T101**	15.86 (0.625)	11.43 (0.450)	11.43 (0.450)	17.78 (0.700)	15.75 (0.621)





RECOMMENDED HOLE PATTERN



T = Contact Plating

- T = **4.** 6µ" gold over 50µ" nickel
- T = **5.** 15µ" gold over 50µ" nickel
- T = **6.** 30µ" gold over 50µ" nickel
- T = **7.** 50µ" gold over 50µ" nickel

CONEXCON Products specifications are subjet to be changed without notice. Please contact Sales Office for further confirmation