

LOW PROFILE PCB JACK SMT TYPE



7641 SERIES. For PCB solder. Side Entry PCB Jack

Features

- Available in 4/4, 6/4, 6/6, 8/8 and 10/10 circuits
- Insulator Material: Glass filled polyester UL 94V-0
- Contacts: Golden phosphor bronze of 0.35 X 0.45 mm.
- Low profile
- Gold plating over nickel in Contact Area.
- Tin plating over nickel in Solder Area
- Mates with FCC-68 modular plugs
- Optional: 4/2 and 6/2 versions

Dimensional Information

Ordering and Dimensional Information

Circuit Size	Part Number	Dimensions		
		A	B	C
4/4	7641 – T441	11.21 (0.442)	7.62 (0.300)	3.81 (0.150)
6/4	7641 – T641	12.96 (0.511)	10.16 (0.400)	3.81 (0.150)
6/6	7641 – T661	12.96 (0.511)	10.16 (0.400)	6.35 (0.250)
8/8	7641 – T881	15.24 (0.600)	11.43 (0.450)	8.89 (0.350)
10/10	7641 – T101	15.24 (0.600)	11.43 (0.450)	11.43 (0.450)

T = Contact Plating

- T = 4.6 μ" gold over 50 μ" nickel
- T = 5.15 μ" gold over 50 μ" nickel
- T = 6.30 μ" gold over 50 μ" nickel
- T = 7.50 μ" gold over 50 μ" nickel

