

RIGHT ANGLE MULTI-PORT JACK WITH LED



7671 SERIES. For PCB Solder. Unshielded

Features

- Available in version 8/8
- Available in 1, 2, 4, 6 y 8 ports
- Mates with plugs FCC-68
- Insulator Material: Thermoplastic; UL94V-0
- Contact Material: Phosphor Bronze wire 0.35 mm. Thickness; Different plating options available

Dimensional Information

| OPCION C | LED 1 | LED 2 |
|----------|------------|------------|
| | RIGHT | LEFT |
| C = 0 | W/O LED | W/O LED |
| C = 1 | GREEN | YELLOW |
| C = 2 | GREEN | W/O LED |
| C = 3 | YELLOW | GREEN |
| C = 4 | GREEN | GREEN |
| C = 5 | YELLOW | YELLOW |
| C = 6 | YELL/GREEN | YELL/GREEN |
| C = 7 | GRREN/RED | GREEN/RED |
| C = 8 | YELLOW | YELL/GREEN |

Ordering and Dimensional Information

| PORTS | Part Number | DIMENSIONS | | | |
|-------|-------------|------------|--------|--------|------|
| | | A | B | C | D |
| 1 | 7671 - T01C | 15.91 | - | 12.70 | 2.54 |
| 2 | 7671 - T02C | 31.66 | 15.75 | 28.45 | 2.37 |
| 4 | 7671 - T04C | 63.16 | 47.25 | 59.94 | 2.37 |
| 6 | 7671 - T06C | 95.26 | 78.75 | 91.45 | 2.67 |
| 8 | 7671 - T08C | 126.16 | 110.25 | 122.94 | 2.37 |

T = Plating of the Pins

- T = 4. 0.15 μ Gold over 1.27 μ Ni.
- T = 5. 0.38 μ Gold over 1.27 μ Ni.
- T = 6. 0.75 μ Gold over 1.27 μ Ni.
- T = 7. 1.27 μ Gold over 1.27 μ Ni.

