

SINGLE ROW VERTICAL SMT SOCKET



8406 SERIES. 2.54 mm. (0.100") pitch. Machined contact.



General Features

- Available in 2 through 40 circuits
- Mates with pin headers 2.54 mm. pitch 8412, 8394, 8398 and 8396 series
- Accept round pin 0.40 mm to 0.56 mm
- Low profile: 4.20 mm.
- With different plating and dimensions options

Materials

- Insulator: PPS black + 30% GF UL 94 V-0
- Contact: Clip (4 fingers): Beryllium copper
- Sleeve: Brass
- Operating temperature. -40°C to +105°C
- RoHS compliant

Dimension Information



Electrical Features

- Voltage rating: < 250V
- Current rating: < 3A
- Contact resistance: < 10 mΩ
- Dielectric withstanding Voltage: 1000 V AC/minute
- Insulation resistance: >1000 MΩ

Mechanical Features

- Insertion force per pin: < 0.20 Kgf (round pin 0.43 mm)
- Withdrawal force per pin: > 0.03 Kgf (round pin 0.43 mm)
- Durability: 500 Cycles

Ordering Information:

8406 - T- XX- 1
1 2 3

1. Connector Series

2. (T) Contact Plating

- T = 13. Selec. gold flash over 30-50μ" Ni overall Recommended Finish
- T = 15. 15μ" selec. gold over 30-50μ" Ni overall
- T = 16. 30μ" selec. gold over 30-50μ" Ni overall

3. (XX) Number of circuits

- Available in 2 through 40 circuits